

NOMINAL HOLE SIZE	PSX: DD SIZE DESCRIPTION	GASKET I.D. (INCHES)	PIPE O.D. ACCOMMODATION RANGE (INCHES)	TAKE-UP CLAMP		MINIMUM SIZE ROUND STRUCTURE (INCHES)	MINIMUM SPAN/RISE STRAIGHT WALL (INCHES)
				QTY	PART #		
REQUIRES BLACK SHORT 7/16 TORQUE WRENCH PRESET TO 12 FT/LBS PART # 850.605							
8	8 QRS STEP "S" PSX: DD	2.20	1.70 TO 2.50	1	600-088	36	16
	8 QRS STEP "R" PSX: DD	3.50	2.75 TO 3.75	1	600-088		
	8 QRS STEP "Q" PSX: DD	4.60	3.75 TO 4.80	1	600-088		
	8 QRS PSX: DD	N/A	1.90 TO 4.80	1	600-088		
9	09-06 PSX: DD	6.45	6.00 TO 6.50	1	600-128	36	17
10	10-06 PSX: DD	6.50	5.50 TO 6.90	1	600-128	36	17
10.5	10.5-06 PSX: DD	6.30	5.70 TO 6.90	1	600-128	36	19
11	11-06 PSX: DD	6.30	5.70 TO 6.90	1	600-128	36	19
	11-08 PSX: DD	8.44	8.00 TO 8.50	1	600-152		
12	12-06 PSX: DD	6.30	5.70 TO 6.90	1	600-128	36	20
	12Y PSX: DD	6.50	5.70 TO 6.90	1	600-128		
	12-08 PSX: DD	8.44	8.00 TO 8.65	1	600-152		
	12M PSX: DD	8.63	8.00 TO 9.10	1	600-152		
	12-11 PSX: DD	9.46	8.60 TO 9.50	1	600-188		
13	13-10 PSX: DD	10.65	9.75 TO 10.50	1	600-188	36	21
14	14M PSX: DD	10.35	9.75 TO 11.10	1	600-188	36	22
REQUIRES BLUE 1/2 TORQUE WRENCH PRESET TO 20 FT/LBS PART # 850.610							
16	16Y PSX: DD	10.75	10.00 TO 11.10	1	600-188	36	24
	16L PSX: DD	12.10	11.36 TO 12.50	1	600-232		
	16M PSX: DD	12.75	12.05 TO 13.30	1	600-232		
18	18Y PSX: DD-2	14.10	13.20 TO 14.50	2	600-296	36	26
	18M PSX: DD-2	15.35	14.60 TO 15.50	2	600-296		
20	20Y PSX: DD	15.50	14..80 TO 16.00	2	600-296	36	28
	20A PSX: DD	16.92	16.00 TO 17.40	2	600-296		
REQUIRES RED 5/8 TORQUE WRENCH PRESET TO 60 FT/LBS PART # 850.632							
22	22L PSX-2: DD	17.80	17.00 TO 18.15	2	600-376	42	30
	22M PSX-2: DD	18.70	18.00 TO 19.20	2	600-376		
24	24L PSX-2: DD	19.55	19.00 TO 19.75	2	600-376	48	32
	24A PSX-2: DD	21.93	21.00 TO 21.50	2	600-376		
26	26L PSX-2: DD	22.18	21.30 TO 22.40	2	600-376	48	34
	26A PSX-2: DD	23.12	22.25 TO 23.25	2	600-456		
28	28L PSX-2: DD	24.31	23.40 TO 24.60	2	600-456	48	36
	28A PSX-2: DD	24.80	24.25 TO 24.80	2	600-456		
30	30L PSX-2: DD	26.32	25.40 TO 26.60	2	600-456	60	42
	30A PSX-2: DD	27.12	26.25 TO 27.40	2	600-456		
32	32L PSX-2: DD	28.32	27.40 TO 28.60	4	600-296	60	44
	32A PSX-2: DD	29.13	28.25 TO 29.40	4	600-296		
34	34L PSX-2: DD	30.33	29.50 TO 30.50	4	600-296	60	46
36	36L PSX-2: DD	31.33	31.00 TO 31.50	4	600-296	72	48
	36A PSX-2: DD	32.08	31.50 TO 32.00	4	600-296		
38	38A PSX-2: DD	33.59	32.70 TO 33.80	4	600-296	72	50
40	40L PSX-2: DD	35.13	34.25 TO 35.50	4	600-376	72	52
	40S PSX-2: DD	36.00	35.50 TO 36.00	4	600-376		
42	42L PSX-2: DD	37.60	37.00 TO 38.00	4	600-376	72	54
	42A PSX-2: DD	38.35	38.00 TO 38.75	4	600-376		
46	46L PSX-2: DD	41.36	41.00 TO 41.75	4	600-376	84	58
48	48L PSX-2: DD	44.35	43.60 TO 44.50	4	600-376	84	62

Preset torque wrenches available from Press-Seal Gasket are required to install all PSX:DIRECT DRIVE Connectors

Protected by one or more of the following patents: 6805359, 7146689, 7263746

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2010.

