

MATERIAL SAFETY DATA SHEET



PRESS-SEAL GASKET CORPORATION
CONCRETE PRODUCTS SUPPLY COMPANY

1-800-348-7325 (219) 436-0521
MAIL TO: P.O. BOX 10482 • FORT WAYNE, INDIANA 46852
SHIP TO: 6935 LINCOLN PARKWAY • FORT WAYNE, INDIANA 46804



Section I PRODUCT INFORMATION

PRODUCT NAME: Underwater Lubricant
CHEMICAL NAME: Formulated Product (Vegetable Oil Grease)
SYNONYMS: N/A
CHEMICAL FAMILY: Calcium Soap FORMULA: N/A

Section II INGREDIENTS

CAS NUMBER	INGREDIENT NAME	% (Wt)	TLV/PEL
68002-73-3	Calcium Oleate	20-30	N/A
61788-67-8	Vegetable Oil	20-30	N/A
	Clay	20-30	N/A
111-46-6	Diethylene Glycol	<10	N/A
	Water	10-15	N/A
68648-22-6	Tall Diethanolamide	0-5	N/A

Section III HAZARD INFORMATION/EXPOSURE LIMIT

	HAZARD INDEX
HEALTH	4 Severe Hazard
FLAMMABILITY	3 Serious Hazard
REACTIVITY	2 Moderate Hazard
	1 Slight Hazard
	0 Minimal Hazard

STATEMENT OF HAZARD: Irritant, Eyes & Skin
WARNING: CAUSES IRRITATION TO EYES
Avoid contact with eyes, skin, and clothing.
Wash thoroughly after use.
NOTE: See Section IV FOR EMERGENCY AND FIRST AID PROCEDURES.

Section IV PHYSICAL DATA

APPEARANCE/ODOR: Amber paste, bland odor
BOILING POINT: > 220 deg. F.
DENSITY: > 1
VAPOR PRESSURE: N/A
VAPOR DENSITY: N/A (air =1)
PH of PRODUCT: N/A
OTHER: Stable 20 - 100 deg. F.

Section V FIRE AND EXPLOSION DATA

FLASHPOINT: > 250 deg. F.
UPPER EXPLOSION LIMIT: N/A
LOWER EXPLOSION LIMIT: N/A
EXTINGUISHING MEDIA: Any standard extinguishing media will be suitable
HAZARDOUS DECOMPOSITION PRODUCTS: None
FIREFIGHTING PROCEDURES OR OTHER INFORMATION: None

Section VI EMERGENCY AND FIRST AID PROCEDURES

In case of contact with eyes, flush eyes with copious volume of water.
If irritation persists, see physician.
In case of contact with skin, wash off with soap and water.
Wash clothing before reuse.
If swallowed, do not induce vomiting. Call a physician immediately.

Section VII REACTIVITY, STORAGE & HANDLING

This product is not water soluble. It is stable.
Hazardous polymerization will not occur.
There are no known decomposition products, under normal use.
Avoid contact with strong oxidizers.
SPECIAL HANDLING INSTRUCTIONS: NONE

Section VIII ENVIRONMENTAL PROTECTION / SPILL AND LEAK PROCEDURES

Spilled material should be contained, then shovelled or vacuumed into drums for disposal in a secure landfill. Flush remaining material to sewage treatment facility, in accordance with applicable regulations.
CAUTION: Spill area may be slippery.

Section IX ADDITIONAL INFORMATION

Not considered a hazardous material under DOT regulations.

Section X WASTE DISPOSAL

*** Non-Biodegradable ***

Flush to sewage treatment facility in accordance with regulations.

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.
IF UNCERTAIN OF LOCAL REQUIREMENTS, CONTACT THE PROPER ENVIRONMENTAL
AUTHORITIES.

CONTAINER DISPOSAL: Offer to reconditioner for recycling.

Section XI ADDITIONAL INFORMATION

Slippery conditions exist when material is spilled, use caution when cleaning up spillage.

Date of preparation: September, 1992
Supersedes March 16, 1989

PRESS-SEAL GASKET CORPORATION, makes no warranty, expressed or implied, regarding the health and accident hazards associated with the use and handling of this product. This information is made available to Buyer only on the express condition that Buyer release PSG from any liability and responsibility therefore. As the information was obtained, in part from our suppliers and their laboratories not under the direction and supervision of PSG. Press-Seal makes no warranty or representation that the information is accurate, reliable, complete or representative and the Buyer may rely thereon only at Buyer's own risk.