


# PSX: Direct Drive

A visual guide for an industry leading pipe-to-manhole connector



## BLACK TORQUE WRENCH



**8-14"**  
Hole size range



**1.7-11.30"**  
Pipe O.D. accomodation

**16"22"**  
Min Span/Rise  
Straight Wall

## BLUE TORQUE WRENCH



**16-20"**  
Hole size range



**10-17.40"**  
Pipe O.D. accomodation

**24"-28"**  
Min Span/Rise  
Straight Wall

## RED TORQUE WRENCH



**22-48"**  
Hole size range



**17-44.50"**  
Pipe O.D. accomodation

**30"-62"**  
Min Span/Rise  
Straight Wall

# EXPANSION SLEEVES



Single adjuster  
for 8" - 26"  
hole sizes



Two adjusters  
for 28" - 32"  
hole sizes



Three adjusters  
for 34" - 48"  
hole sizes

## SPECIFICATIONS

**C923**

**CI478**

**F2510**

**D2321**

Section 7.10 Manhole Connections

## PIPE TYPES

**PVC**

**RCP**

**HDPE**

**CI/DI**

\*More pipes are available

# STAINLESS STEEL TAKE-UP CLAMPS




**1** For pipe OD's  
ranging from  
1.70" to 23.25"

\*A 2nd take-up clamp is optional



**2** For pipe OD's  
ranging from  
23.40" to 27.40"



**4** For pipe OD's  
ranging from  
27.40" to 44.50"



This graphic is for reference and informal purposes only and should be taken as such. Detailed information should be sought through our website or printed catalog.  
Press-Seal Corporation • 2424 West State Blvd • Fort Wayne, IN • 4608 • www.press-seal.com • (260) 436-0521  
2017 • All Rights Reserved