

EZ-STIK #4 PRIMER

What It Is

The EZ-Stik #4 Primer is a solvent based mixture of rubber adhesives, low viscosity gel-type.

Its primary use is to promote adhesion of butyl tapes and wraps to concrete surfaces and is designed for dripless paint brush application to concrete surfaces.

How It Works

- Enhance's bond between surface & wrap.
- Helps to seal joint wrap on the porous substrate of the manhole.
- Provides a clean smooth surface that's easy for wrap to bond to.

Why It's Better

- Can be brushed or rolled on to concrete structures.
- Properties help promote adhesion of butyl tapes or wraps.
- Can be used on smooth or rough textured concrete surfaces.



Instructions

1. Brush a thin film of #4 Primer on concrete surface
2. Air dry approximately 10 minutes
3. Then apply butyl wrap
4. Coverage is approximately 100-120 sq. ft./gal.

Where To Use

EZ-Stik #4 Primer is recommended for use when concrete surfaces are:

- Fresh
- Damp or wet
- Dusty
- Gritty or rough textured
- Cracked
- Has mold release present

Or otherwise not suitable for good matting of the seal.



EZ-STIK #4 PRIMER

PROPERTIES AND HANDLING

PHYSICAL PROPERTIES

- Coverage Approximately 100-120 sq. ft./gal.
- Color & Odor..... Black / Faint odor characteristic of rubber and petroleum solvent.
- Appearance Free from lumps and grains. Dried ready to use surface will be flat (not shiny).
- Flash Point..... 25°F (-4 C), Red label required. UN1133.
- Solids Content 25%
- Shelf Life..... 1yr - stored in unopened original container.

SPECIAL HANDLING

- Store and apply at temperatures from 32°F (0 C) to 110°F (43 C).
- All pails and other containers should be closed to prevent evaporation of contents.
- Pails should be stirred well before use to homogenize all ingredients.
- Clean up with mineral spirits if required.
- Use in well ventilated area.
- Keep away from fire and open flame.

EZ-STIK #4 PRIMER is available in 5 gallon pails (45 per pallet) or in 1 gallon cans (6 per case)

Must ship via truck freight due to flammability.



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2022.

Phone: 800-348-7325
Fax: (260) 436-1908

PRESS-SEAL CORPORATION
Protecting Our Planet's Clean Water Supply
ISO 9001: Registered • Version 03.21.22.8.46

Email: sales@press-seal.com
Web: www.press-seal.com