

# EZ-WRAP PAK

## PRECUT EXTERIOR BUTYL RUBBER JOINT WRAP

### What It Is

EZ-Wrap Pak is a package of precut sections of 6" wide EZ-Wrap Plastic Joint Wrap. Each package contains sections of wrap cut perfectly for 48" (1200 mm), 60" (1500 mm), or 72" (1800 mm) manhole joints, and the necessary amount of spray adhesive primer.

EZ-Wrap is a waterproofing membrane butyl adhesive tape designed to provide high strength, watertight seals on properly primed concrete surfaces and concrete structure joints. A release liner for the rubber backing makes for easy installation for a variety of applications.

### How It Works

- Exterior surface is cleaned and free of debris.
- Spray adhesive is applied.  
(EZ-Stik #4 primer can be applied first if required)
- Pre-cut wrap already prepared for proper size manhole.
- Release paper is removed and wrap is applied to structure.

### Why It's Better

- No cutting in field saves contractor labor
- Precisely cut rolls greatly reduces loss and waste.
- Provided spray adhesive allows for quick installation of wrap on structures.
- Coated release paper for easy installation.
- Better all-weather performance.
- High quality butyl rubber base.
- Adhesion to a variety of surfaces such as concrete, steel or even glass.



### Where To Use

- Manholes
- Wet wells
- Square pump and lift stations
- Stormwater structures
- On-site treatment structures
- Junction chambers
- Grease interceptors



# EZ-WRAP PAK

## SUBMITTAL SPECIFICATIONS

---

### BUTYL JOINT WRAP WITH PLASTIC BACKING:

The joints and/or joining surfaces of the structures shall be sealed with a butyl-rubber-based tape. The material shall be EZ-WRAP Plastic as supplied by PRESS-SEAL CORPORATION, Fort Wayne, Indiana, or approved equal. The butyl component of the tape shall consist of 50% (min.) butyl rubber, shall contain 2% or less volatile matter, and shall be .050" (1.3 mm) thick. The backing component shall be high-density polyethylene film. A release paper may be utilized.

For manholes, the tape width shall be 6" (150 mm) wide. The tape shall be overlapped at least twice its width. The tape shall not be stretched during application. Primer and/or adhesive as recommended by the tape supplier shall be employed for adverse, critical, or other applications.

Testing of joints and compliance with construction requirements shall be conducted in strict conformance with the requirements of the sealant supplier.

---

## Product Performance

---

EZ-WRAP BUTYL JOINT WRAP meets or exceeds all requirements of the following Standards, Specifications and/or Test Methods:

- ASTM C 877 (Type III) - Standard Specification for External Sealing Bands for Concrete Pipe, Manholes, and Precast Box Sections



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2022.

Phone: 800-348-7325  
Fax: (260) 436-1908

**PRESS-SEAL CORPORATION**  
*Protecting Our Planet's Clean Water Supply*  
ISO 9001: Registered • Version 02.18.22.4.57

Email: [sales@press-seal.com](mailto:sales@press-seal.com)  
Web: [www.press-seal.com](http://www.press-seal.com)

# EZ-WRAP PAK

## SELECTION GUIDE

EZ WRAP-PAKS (6" (150 mm) wide Plastic)			
Manhole Size	Roll Length	No. Rolls	Part No.
<b>48" ID X 5"</b>	<b>16 ft</b>	6	276.616
1200 x 125 mm	4.9 m		
<b>60" ID X 6"</b>	<b>20 ft</b>	5	276.620
1500 x 150 mm	6.1 m		
<b>72" ID X 7"</b>	<b>24 ft</b>	4	276.624
1800 x 175 mm	7.3 m		

