

HDPE HOLE FORMERS

Low Draft Taper for Pipe-To-Manhole



Straight Wall Structures

- Available in diameters from 8" to 28" (200 – 914 mm).
- 4" to 8" wall thickness (100 – 200 mm).
- Magna-Former Magnetic Holding.

What It Is

Press-Seal HDPE Hole Formers are nearly indestructible. Made with low draft taper for use with pipe to manhole connectors. Available for round and straight wall structures. Used with our patented magnetic holding device.

Standard Round Manholes

- Available in diameters from 8" to 36" (200 – 915 mm).
- Manhole ID's of 30", 48", 60", and 72" (750, 1200, 1500, 1800 mm).
- Manhole wall thicknesses of 3-1/2", 4", 5", 6", 7", and 8" (90, 100, 125, 150, 175, 200 mm).

Features & Benefits

- Made of tough, resilient high-density polyethylene lasting longer than fiberglass hole formers
- Heavy hollow body with mounting ring
- Low draft 1.5° taper for use with PSX: Direct Drive and other boot-type flexible connectors
- Non-stick surface and low draft make removal easy
- Can be installed with magnetic holders or threaded anchors
- When used with our magnet system, creates perfect placement every time saving set up time
- Magnet system is interchangeable with all sizes and can also be used with other Press-Seal polyethylene connector mandrel systems such as the Cast-A-Seal 12-08 and 603 product lines.

INFORMATION

All HDPE hole formers can be ordered with Magna-Former magnetic holding system

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2022.

