

CLASSIC PIPE LUBRICANT

LUBRICATION FOR GASKET JOINTS

What It Is

Our classic pipe gasket joint lubricant comes in two different varieties – regular and underwater.

Both are specially formulated for the rigorous environment of underground pipe jointing and contain no petroleum that may damage some rubber gasket compounds.

**DESIGNED SPECIFICALLY
FOR LUBRICATING
GASKET JOINTS ON
PIPE AND MANHOLES**



Underwater Lube

- Specially formulated for the most demanding installation conditions.
- Designed to meet wash test for subaqueous lubricants in accordance with ASTM C 497, Section 12.3.
- Resists wash-off.
- Freeze-resistant.
- Meets durometer and volume change test requirements in accordance with ASTM C 497, Section 12.2 and D-2240.
- Consistency stable from + 20°F (-7°C) to + 90°F (+ 32°C).
- Available in 1 gallon (3.9 L) (8 lb.) and 3 1/2 gallon (13.5 L) (27.5 lb.) pails.

Regular Lube

- Our original pipe joint lube.
- Meets durometer and volume change test requirements in accordance with ASTM C 497, Section 12.2 and D-2240.
- Provides reliable, economical lubrication in all climates.
- Highly freeze-resistant.
- Consistency stable from 0°F (-17°C) to ± 150°F (± 65°C).
- Available in 1 gallon (3.9 L) (8 lb.) and 3 1/2 gallon (13.5 L) (25 lb.) pails.
- NSF approved for use in potable water systems.

Type	Size		Weight		Part No.	Pallet Qty.
	Gallons	Liters	Pounds	Kilograms		
Underwater	1 gal.	3.9 L	8 lbs.	3.63 kg	130.17	144
Underwater	3.5 gal.	13.5 L	27.5 lbs.	12.5 kg	130.525	48
Regular	1 gal.	3.9 L	8 lbs.	3.63 kg	130.107	144
Regular	3.5 gal.	13.5 L	25 lbs.	12.5 kg	130.105	48



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2022.

Phone: 800-348-7325
Fax: (260) 436-1908

PRESS-SEAL CORPORATION
Protecting Our Planet's Clean Water Supply
ISO 9001: Registered • Version 03.21.22.9.04

Email: sales@press-seal.com
Web: www.press-seal.com