

POLYLUBE PIPE LUBRICANT

LUBRICATION FOR GASKET JOINTS

What It Is

Polylube is specially formulated for the rigorous environments of underground pipe jointing and compression seal connections.

From all-weather to underwater, our PolyLube line provides you three options to meet your most demanding needs.

How It Works

- Joint is cleaned and free of debris
- Gasket is stretched onto pipe
- Lubrication is applied (see installation instructions)

Why It's Better

- Designed specifically for lubricating gasket joints on pipe
- Formulated for the most demanding installation conditions
- Meets durometer and volume change test requirements in accordance with ASTM D-2240, C-497, Section 12.2 and D-471



POLYLUBE 32

- **ECONOMICAL**
- **32°F to 140°F**
- **ECO-FRIENDLY**
- **NSF APPROVED**

POLYLUBE ULTRA

- **ALL WEATHER**
- **10°F to 120°F**
- **ECO-FRIENDLY**
- **NSF APPROVED**

POLYLUBE SUB-AQUEOUS

- **UNDERWATER**
- **32°F to 120°F**
- **RESISTS WASH OFF**

PACKAGING	WEIGHT	CASE QTY	CASE WEIGHT	SKID QTY	SKID WEIGHT	TRUCK QTY (Pallets)
1 QUART	2lbs	12	24	48 (cases)	1,152	22
1 GALLON	8lbs	4	32	36 (cases)	1,152	22
3.5 GALLON	28lbs	N/A	N/A	48 (each)	1,200	22
5 GALLON	40lbs	N/A	N/A	48 (each)	1,920	20

