

PSX: DIRECT DRIVE NITRILE

PIPE TO MANHOLE & TANK CONNECTOR

What It Is

PSX: Direct Drive Nitrile is a high-performance flexible pipe-to-manhole connector that offers easy installation and long-term performance in one convenient product.

With the added ability to resist common underground contaminants including hydrocarbons and many mixed chemistries.

Whether you core or cast your holes, PSX: Direct Drive Nitrile fits right into your production methods, ready to seal your toughest applications every time.

How It Works

- The connector fits into a cast or cored hole.
- A power sleeve made from tempered series 304 stainless steel expands with a certified installation wrench.
- Take-up clamps made from series 304 stainless steel with quick adjusting screws secure the connector to the pipe.

Why It's Better

- Nitrile rubber resists most chemicals and hydrocarbons found in effluent and soils.
- Safely install from outside of the manhole preventing falls from crawling down into structures.
- All stainless-steel components with no welds or rivets creating a stronger product.
- Precision molding provides accurate compensation for hole size variations.
- Contains chemically resistant stainless steel.
- Contractor can save time and money by backfilling immediately.



Where To Use

- Manholes
- Wet wells
- Square pump and lift stations
- Stormwater structures
- On-site treatment structures
- Junction chambers
- Grease interceptors
- Vaults



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2026.

Phone: 800-348-7325
Fax: (260) 436-1908

PRESS-SEAL CORPORATION
Protecting Our Planet's Clean Water Supply
ISO 9001: Registered • 10.29.26.1.39

Email: sales@press-seal.com
Web: www.press-seal.com

PSX: DIRECT DRIVE NITRILE

SUBMITTAL SPECIFICATIONS

Pipe-to-Manhole and Structure Connector Specification for Sanitary and Storm Sewer Applications:

All pipe-to-manhole and structure connections shall meet and or exceed ASTM C 923, Standard Specification for Resilient Connectors Between Reinforced Concrete Manholes, Structures, Pipes and laterals.

All mechanical devices, including castings, bolt assemblies, adjusters shall use non-magnetic 300 series stainless steel with no welds or rivets in its assemblies.

The installation of the connector shall be accomplished at one time and shall require no additional adjustments or installation at a later time to insure a watertight seal.

Take up clamps shall use non-magnetic 304 series stainless steel and be installed in the field using a T-Handle Torque wrench set to 60 inch-pounds and installation shall follow manufacturer's instructions.

The connector shall be PSX: Direct Drive Nitrile and PSX: Nylo Drive Nitrile as manufactured by Press-Seal Corporation of Fort Wayne, IN or approved equal.

Product Performance

PSX: Direct Drive - Nitrile meets or exceeds all requirements of the following specifications and/or test methods:

- ASTM C 923 - Standard Specification for Resilient Connectors Between Reinforced Concrete Manhole Structures, Pipes, and Laterals
- ASTM C 1619 Class D (Material Spec)
- ASTM C 1244 - Standard Test Method for Concrete Sewer Manholes by the Negative Air Pressure (Vacuum) Test
- ASTM C 1478 - Standard Specification for Storm Drain Resilient Connectors Between Reinforced Concrete Storm Sewer Structures, Pipes and Laterals
- ASTM F 2510 - Standard Specification for Resilient Connectors Between Reinforced Concrete Manhole Structures and Corrugated High Density Polyethylene Drainage Pipes

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2026.

Phone: 800-348-7325
Fax: (260) 436-1908

PRESS-SEAL CORPORATION
Protecting Our Planet's Clean Water Supply
ISO 9001: Registered • 10.29.26.1.39

Email: sales@press-seal.com
Web: www.press-seal.com



PSX: DIRECT DRIVE NITRILE

SELECTION GUIDE

PSX: DD SIZE DESCRIPTION	HOLE SIZE RANGE		PIPE O.D. ACCOMMODATION RANGE INCHES (mm)		GASKET I.D.		TAKE-UP CLAMP		NUMBER OF EXPANSION SLEEVE MECHANISMS	MINIMUM SIZE ROUND STRUCTURE (INCHES)
	INCH	mm			INCH	mm	QTY	PART #		
REQUIRES BLACK SHORT 7/16 TORQUE WRENCH PRESET TO 12 FT/LBS PART # 850.605										
8 QRS STEP "S" NITRILE 8 QRS STEP "R" NITRILE 8 QRS STEP "Q" NITRILE 8 QRS PSX: NITRILE	8.00 - 8.20	203 - 206	1.70" TO 2.50" 2.75" TO 3.75" 3.75 "TO 4.80" 1.90 "TO 4.80"	43 - 64 mm 70 - 95 mm 95 - 122 mm 48 - 122 mm	2.20 3.50 4.60 N/A	56 89 117 N/A	1 1 1 1	600.088 600.088 600.088 600.088	1	24
12Y PSX: DD NITRILE 12M PSX: DD NITRILE	12.00 - 12.20	305 - 310	5.70" TO 6.90" 8.00" TO 9.10"	145 - 175 mm 203 - 231 mm	6.30 8.63	160 219	1 1	600.128 600.152	1	24
14M PSX: DD NITRILE	14.00 - 14.20	356 - 361	9.75" TO 11.10"	248 - 282 mm	10.35	263	1	600.188	1	30
REQUIRES BLUE 1/2 TORQUE WRENCH PRESET TO 20 FT/LBS PART # 850.610										
16L PSX: DD NITRILE 16M PSX: DD NITRILE	16.00 - 16.20	406 - 411	11.36" TO 12.50" 12.05" TO 13.30"	289 - 318 mm 306 - 338 mm	12.10 12.75	307 324	1 1	600.232 600.232	1	36
18M PSX-2: DD NITRILE	18.00 - 18.20	457 -462	14.60" TO 15.50"	371 - 394 mm	15.35	390	2	600.296	1	36
REQUIRES RED 5/8 TORQUE WRENCH PRESET TO 60 FT/LBS PART # 850.632										
22M PSX-2: DD NITRILE	22.00 - 22.20	559 - 564	18.00" TO 19.20"	457 - 488 mm	18.70	475	2	600.376	1	42



Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors. Copyright 2026.

Phone: 800-348-7325
Fax: (260) 436-1908

PRESS-SEAL CORPORATION
Protecting Our Planet's Clean Water Supply
ISO 9001: Registered • 10.29.26.1.39

Email: sales@press-seal.com
Web: www.press-seal.com